

## Three-Row Roller Bearing Slewing Ring

	Basic Type			Configuration Size			Mounting Size				Structural Size			Gear Data			Ext Gear		Int Gear		Tangential Tooth Load		Reference weight kg
	Toothless $D_L$ mm	Ext Toothing $D_L$ mm	Int Toothing $D_L$ mm	$D$ mm	$d$ mm	$H$ mm	$D_1$ mm	$D_2$ mm	$n$	$\emptyset$ mm	$n_1$	$H_1$	$h$ mm	$b$ mm	$x$	$m$ mm	$D_e$ mm	$z$	$D_e$ mm	$z$	Normalizing $Z_4$ 10 N	Tempering $Z_4$ 10 N	
130.25.500	131.25.500	133.25.500	634	366	148	598	402	24	18	4	138	32	80		5	664	130	337	68	5.0	6.7	224	
	132.25.500	134.25.500													6	664.8	108	338.4	57	6.0	8.0		
130.25.560	131.25.560	133.25.560	694	426	148	658	462	24	18	4	138	32	80		5	724	142	397	80	5.0	6.7	240	
	132.25.560	134.25.560													6	724.8	118	398.4	67	6.0	8.0		
130.25.630	131.25.630	133.25.630	764	496	148	728	532	28	18	4	138	32	80		6	808.8	132	458.4	77	6.0	8.0	270	
	132.25.630	134.25.630													8	806.4	98	459.2	58	8.0	11.0		
130.25.710	131.25.710	133.25.710	844	576	148	808	612	28	18	4	138	32	80	+0.5	6	886.8	145	536.4	90	6.0	8.0	300	
	132.25.710	134.25.710													8	886.4	108	539.2	68	8.0	11.0		
130.32.800	131.32.800	133.32.800	964	636	182	920	680	36	22	4	172	40	120	+0.5	8	1006.4	123	595.2	75	12.1	16.7	500	
	132.32.800	134.32.800													10	1008	98	594	60	15.1	20.9		
130.32.900	131.32.900	133.32.900	1064	736	182	1020	780	36	22	4	172	40	120	+0.5	8	1102.4	135	691.2	87	12.1	16.7	600	
	132.32.900	134.32.900													10	1108	108	694	70	15.1	20.9		
130.32.1000	131.32.1000	133.32.1000	1164	836	182	1120	880	40	22	5	172	40	120	+0.5	10	1218	119	784	79	15.1	20.9	680	
	132.32.1000	134.32.1000													12	1221.6	99	784.8	66	18.1	25.1		
130.32.1120	131.32.1120	133.32.1120	1284	956	182	1240	1000	40	22	5	172	40	120	+0.5	10	1338	131	904	91	15.1	20.9	820	
	132.32.1120	134.32.1120													12	1341.6	109	904.8	76	18.1	25.1		
130.40.1250	131.40.1250	133.40.1250	1445	1055	220	1393	1107	45	26	5	210	50	150	+0.5	12	1509.6	123	988.8	83	22.9	31.4	1200	
	132.40.1250	134.40.1250													14	1509.2	105	985.6	71	26.3	36.6		
130.40.1400	131.40.1400	133.40.1400	1595	1205	220	1543	1257	45	26	5	210	50	150	+0.5	12	1665.6	136	1144.8	96	22.9	31.4	1300	
	132.40.1400	134.40.1400													14	1663.2	116	1139.6	82	26.3	36.6		

130.40.1600	131.40.1600	133.40.1600	1795	1405	220	1743	1457	48	26	6	210	50	150	+0.5	14	1873.2	131	1335.6	96	26.3	36.6	1520
	132.40.1600	134.40.1600													16	1868.8	114	1334.4	84	30.2	41.7	
130.40.1800	131.40.1800	133.40.1800	1995	1605	220	1943	1657	48	26	6	210	50	150	+0.5	14	2069.2	145	1531.6	110	26.3	36.6	1750
	132.40.1800	134.40.1800													16	2076.8	127	1526.4	96	30.2	41.7	
130.45.2000	131.45.2000	133.45.2000	2221	1779	231	2155	1845	60	33	6	219	54	160	+0.5	16	2300.8	141	1702.4	107	32.2	44.5	2400
	132.45.2000	134.45.2000													18	2300.4	125	1699.2	95	36.2	50.1	
130.45.2240	131.45.2240	133.45.2240	2461	2019	231	2395	2085	60	33	6	219	54	160	+0.5	16	2556.8	157	1926.4	121	32.2	44.5	2700
	132.45.2240	134.45.2240													18	2552.4	139	1933.2	108	36.2	50.1	
130.45.2500	131.45.2500	133.45.2500	2721	2279	231	2655	2345	72	33	8	219	54	160	+0.5	18	2822.4	154	2185.2	122	36.2	50.1	3000
	132.45.2500	134.45.2500													20	2816	138	2188	110	40.2	55.6	
130.45.2800	131.45.2800	133.45.2800	3021	2579	231	2955	2645	72	33	8	219	54	160	+0.5	18	3110.4	170	2491.2	139	36.2	50.1	3400
	132.45.2800	134.45.2800													20	3116	153	2488	125	40.2	55.6	
130.50.3150	131.50.3150	133.50.3150	3432	2868	270	3342	2958	72	45	8	258	65	180	+0.5	20	3536	174	2768	139	45.2	62.6	5000
	132.50.3150	134.50.3150													22	3537.6	158	2758.8	126	49.8	68.9	
130.50.3550	131.50.3550	133.50.3551	3832	3268	270	3742	3358	72	45	8	258	65	180	+0.5	20	3936	194	3168	159	45.2	62.6	5600
	132.50.3550	134.50.3550													22	3933.6	176	3154.8	144	49.8	68.9	
130.50.4000	131.50.4000	133.50.4000	4282	3718	270	4192	3808	80	45	8	258	65	180	+0.5	22	4395.6	197	3616.8	165	49.8	68.9	6400
	132.50.4000	134.50.4000													25	4395	173	3610	145	56.5	78.3	
130.50.4500	131.50.4500	133.50.4500	4782	4218	270	4692	4308	80	45	8	258	65	180	+0.5	22	4901.6	220	4122.8	188	49.8	68.9	7100
	132.50.4500	134.50.4500													25	4895	193	4110	165	56.5	78.3	